

5

The present invention provides an improved data processing system and in particular a method and apparatus for manipulating data. Still more particularly, the present invention provides a method, apparatus, and computer implemented instructions for identifying actions that may be performed for an object.

The use of data processing systems has become widespread and pervasive in society. The interface through which a user interacts with a data processing system has advanced from the entry of command line commands to graphical user interfaces (GUIs). A graphical user interface (GUI) is a graphics-based user interface that incorporates icons, pull-down menus and a mouse. The GUI has become the standard way users interact with a computer. The GUI is used to perform actions such as, for example, start programs, terminate programs, communicate with other users at other data processing systems, and data manipulation. These actions are accomplished by the user employing input devices such as, for example, a mouse and a keyboard. Objects representing data and programs may be represented on the GUI using icons. Oftentimes, a list of actions that may be performed on an object are presented to the user in response to some input, such as a selection of a right

The actions that may be performed on an object are numerous. For example, a user may copy, cut, delete, paste, run, export, or move an object. These actions may be presented to the user to allow the user to identify what actions may be taken and to provide an interface to execute a selected action. These actions are commonly presented in a pop-up menu for user selection.

10 Currently, the actions that are presented to the user are
predetermined and not easily changed. The actions that
are associated with an object are hard coded. Hard coded
software is software that is programmed to perform a
fixed number of tasks without regard to future
15 flexibility. This type of programming is very easy to
perform and is the ideal kind of programming for one-time
jobs. Such programs typically use a fixed set of values
and may only work with certain types of devices. The
problem with these types of programs is that one-time
20 programs often become widely used, even in day-to-day
operations, but they are difficult to change because the
routines have not been generalized to accept change.
Changing actions allowed on an object are difficult and
require reinstalling or recompiling a program. The
25 mechanism of the present invention also supports runtime
determination of actions against object types when both
the object type and related actions are not known at
creation of the launching code.

Therefore, it would be advantageous to have an improved method, apparatus, and computer implemented instructions for determining actions that can be performed with an object.

Docket No. AUS920010498US1

SUMMARY OF THE INVENTION

5 The present invention provides a method, apparatus,
and computer implemented instructions for presenting
actions associated with an object displayed in a
graphical user interface in a data processing system.
Actions are dynamically associated with the object. In
10 response to a selection of the object, the actions are
presented in the graphical user interface.

Questions and answers about the new law.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 is a pictorial representation of a data processing system in which the present invention may be implemented in accordance with a preferred embodiment of the present invention;

15 **Figure 2** is a block diagram of a data processing
system in which the present invention may be implemented;

Figure 3 is a diagram illustrating components used to dynamically determine actions that can be performed on an object in accordance with a preferred embodiment of the present invention;

Figure 4 is a diagram of a graphical user interface in which actions are presented to a user in accordance with a preferred embodiment of the present invention;

Figure 5 is a flowchart of a process used for
25 registering actions in accordance with a preferred
embodiment of the present invention;

Figure 6 is a flowchart of a process used for adding menu items for a Java class in accordance with a preferred embodiment of the present invention;

30 **Figure 7** is a flowchart of a process used for
populating a collection for a pop-up menu in accordance
with a preferred embodiment of the present invention; and

Docket No. AUS920010498US1

Figure 8 is a flowchart of a process used for executing an action in accordance with a preferred embodiment of the present invention.

092500-062901

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures and in particular
5 with reference to **Figure 1**, a pictorial representation of
a data processing system in which the present invention
may be implemented is depicted in accordance with a
preferred embodiment of the present invention. A
computer **100** is depicted which includes system unit **102**,
10 video display terminal **104**, keyboard **106**, storage devices
108, which may include floppy drives and other types of
permanent and removable storage media, and mouse **110**.
Additional input devices may be included with personal
computer **100**, such as, for example, a joystick, touchpad,
15 touch screen, trackball, microphone, and the like.
Computer **100** can be implemented using any suitable
computer, such as an IBM eServer pSeries computer or
IntelliStation computer, which are products of
International Business Machines Corporation, located in
20 Armonk, New York. Although the depicted representation
shows a computer, other embodiments of the present
invention may be implemented in other types of data
processing systems, such as a network computer. Computer
100 also preferably includes a graphical user interface
25 (GUI) that may be implemented by means of systems
software residing in computer readable media in operation
within computer **100**.

With reference now to **Figure 2**, a block diagram of a
data processing system is shown in which the present
30 invention may be implemented. Data processing system **200**
is an example of a computer, such as computer **100** in

Figure 1, in which code or instructions implementing the processes of the present invention may be located. Data processing system **200** employs a peripheral component interconnect (PCI) local bus architecture. Although the depicted example employs a PCI bus, other bus architectures such as Accelerated Graphics Port (AGP) and Industry Standard Architecture (ISA) may be used. Processor **202** and main memory **204** are connected to PCI local bus **206** through PCI bridge **208**. PCI bridge **208** also may include an integrated memory controller and cache memory for processor **202**. Additional connections to PCI local bus **206** may be made through direct component interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter **210**, small computer system interface (SCSI) host bus adapter **212**, and expansion bus interface **214** are connected to PCI local bus **206** by direct component connection. In contrast, audio adapter **216**, graphics adapter **218**, and audio/video adapter **219** are connected to PCI local bus **206** by add-in boards inserted into expansion slots. Expansion bus interface **214** provides a connection for a keyboard and mouse adapter **220**, modem **222**, and additional memory **224**. SCSI host bus adapter **212** provides a connection for hard disk drive **226**, tape drive **228**, and CD-ROM drive **230**. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

An operating system runs on processor **202** and is used to coordinate and provide control of various components within data processing system **200** in **Figure 2**. The operating system may be a commercially available operating system such as Windows 2000, which is available from

Microsoft Corporation. An object oriented programming system such as Java may run in conjunction with the operating system and provides calls to the operating system from Java programs or applications executing on

5. data processing system **200**. "Java" is a trademark of Sun Microsystems, Inc. Instructions for the operating system, the object-oriented programming system, and applications or programs are located on storage devices, such as hard disk drive **226**, and may be loaded into main memory **204** for

10 execution by processor **202**.

Those of ordinary skill in the art will appreciate that the hardware in **Figure 2** may vary depending on the implementation. Other internal hardware or peripheral devices, such as flash ROM (or equivalent nonvolatile

15 memory) or optical disk drives and the like, may be used in addition to or in place of the hardware depicted in **Figure 2**. Also, the processes of the present invention may be applied to a multiprocessor data processing system.

20 For example, data processing system **200**, if optionally configured as a network computer, may not include SCSI host bus adapter **212**, hard disk drive **226**, tape drive **228**, and CD-ROM **230**, as noted by dotted line **232** in **Figure 2** denoting optional inclusion. In that

25 case, the computer, to be properly called a client computer, must include some type of network communication interface, such as LAN adapter **210**, modem **222**, or the like. As another example, data processing system **200** may be a stand-alone system configured to be bootable without

30 relying on some type of network communication interface, whether or not data processing system **200** comprises some type of network communication interface. As a further

example, data processing system **200** may be a personal digital assistant (PDA), which is configured with ROM and/or flash ROM to provide nonvolatile memory for storing operating system files and/or user-generated data.

The depicted example in **Figure 2** and above-described examples are not meant to imply architectural limitations. For example, data processing system **200** also may be a notebook computer or hand held computer in addition to taking the form of a PDA. Data processing system **200** also may be a kiosk or a Web appliance. The processes of the present invention are performed by processor **202** using computer implemented instructions, which may be located in a memory such as, for example, main memory **204**, memory **224**, or in one or more peripheral devices **226-230**.

The present invention provides a method, apparatus, and computer implemented instructions for dynamically determining actions that are to be associated with an object. The mechanism of the present invention involves non hard-coded software, which is data independent with respect to the mappings of actions and their associations or mappings to objects. This type of software is written such that any data that can possibly be changed should be stored in a database and not "hard wired" into the code of the program. When values change or are added only the database item is altered, which is a simple task, rather than recompiling programs.

In these examples, the mechanism is implemented in the Java programming language. Mappings between actions to perform and an object's class type identify a set of allowable actions for a given object. This determination

may be made at runtime. This mechanism allows existing relationships or associations of actions and objects to be determined at runtime based on the saved class type to actions' mappings. Examples of object types include security objects, such as roles, accounts, capabilities, principals, and persons. Other objects types may be, for example, Java Naming Directory Interface (JNDI) objects, such as javax.naming.Context (a folder) and javax.naming.directory.DirContext (a folder with attributes). These object types also may include an IP address, an IP node, and a gateway.

Turning next to **Figure 3**, a diagram illustrating components used to dynamically determine actions that can be performed on an object is depicted in accordance with a preferred embodiment of the present invention. The components illustrated in **Figure 3** may be found in a data processing system, such as, for example, data processing system **200** in **Figure 2**.

Classes **300** are classes for objects presented in GUI **302**. Menu process **304** provides a mechanism to generate menus of actions that can be performed on objects. Menu process **304** receives classes **300** and dynamically determines which actions should be associated in preparation for displaying a pop-up menu. In these examples, menus are the form in which the actions are presented to a user. These examples are not meant to limit the fashion in which actions associated with objects can be presented. These associations are determined at runtime or at the time the program is executed in these examples. In this manner, actions may be added and removed from associations with objects such that the effects of these changes are presented to the

5

10

15

20

25

30

folder **408** may be changed and the change will be reflected the next time the program is started.

Depending on the implementation, some actions may be hard-coded while others are dynamically determined. The

5 two are combined to make the final pop-up menu. Examples of hard-coded actions in the file system are rename and remove. Examples of dynamically-determined actions are create subdirectory, view, and execute.

Figures 5-8 below illustrate processes used to dynamically identify actions associated with objects and generate a presentation of these actions. The flowcharts in **Figures 5-8** are presented for an implementation of the present invention in the Java programming language. With reference now to **Figure 5**, a flowchart of a process used for registering actions is depicted in accordance with a preferred embodiment of the present invention. The process illustrated in **Figure 5** occurs prior to runtime of a program in a registration phase. The source of the registered material may be, for example, XML, a GUI, or a command line. In these examples, the process in **Figure 5** stores data registering a Java class and its associated actions in a data structure, such as a database or a flat file on a file system.

The process begins with a determination as to whether an unprocessed fully-qualified Java class, which can have an action, is present (step **500**). A fully qualified Java class name includes the Java package in which it resides as a prefix. Most Java classes reside in packages to ensure that there is no name collision between two classes produced by two different companies, divisions, etc. For instance, the Java language has a standard class named "String". The fully-qualified class

15

20

25

The process begins by passing a Java object in from an application from a source (step **600**). This source may be, for example, an explorer, a tree, or a table. Next, an empty collection for pop-up menu items is created (step **602**). This collection also is referred to as a pop-up menu items collection. Then, the Java object's class is retrieved (step **604**). Actions are added to the pop-up menu items collection for the Java class (step

15

Turning next to **Figure 7**, a flowchart of a process used for populating a collection for a pop-up menu is depicted in accordance with a preferred embodiment of the present invention. The process illustrated in **Figure 7** may be implemented in a menu process, such as menu process **304** in **Figure 3**. This process is used to store action information in a collection and may call itself in a recursive fashion.

The process begins by retrieving related actions for the string name for the Java class (step **700**). In these examples, the related actions are retrieved from a database or a flat file. The actions are stored using information generated by registration of classes as illustrated in **Figure 5** above. These actions are in the form of action definitions in this example. Next, a determination is made as to whether an unprocessed action definition is present (step **702**). If unprocessed action definitions are present, an unprocessed action definition is selected for processing (step **704**). The text for the action is looked up using a ResourceBundle and a key for the registered action using standard Java logic (step **706**). A string name for the Java class for the action is retrieved from the registered information (step **708**). Then, the action text and the Java class string name are saved in the collection (step **710**) with the process then

Turning back to step **702**, if unprocessed action definitions are not present, all of the action definitions for the Java class have been processed. At this point, a determination is made as to whether an unprocessed Java superclass is present for this Java class (step **712**). A superclass is a parent class to a class. If an unprocessed Java superclass is present, this superclass is selected for processing (step **714**). Pop-up menu items are added for this Java superclass (step **716**) with the process then returning to step **712** as described above. Step **716** is a recursive call to the process in **Figure 7** for the Java superclass.

With reference again to step **712**, if unprocessed Java superclasses are absent, a determination is made as to whether an unprocessed interface implemented by the Java class is present (step **718**). An interface, as used with respect to the description of **Figure 7**, defines a set of methods and constants to be implemented by another object. If an unprocessed interface implemented by the Java class is present, the unprocessed interface is selected for processing (step **720**). Pop-up menu items for this interface are added by recursively calling the process in **Figure 7** (step **722**) with the process then returning to step **718**. Otherwise, the process terminates. In steps **716** and **722**, the recursive call initiates the process in **Figure 7**. The actions retrieved, however, are for the superclass or the interface rather than the original Java class when the

process in **Figure 7** is first called.

With reference now to **Figure 8**, a flowchart of a process used for executing an action is depicted in accordance with a preferred embodiment of the present invention. The process illustrated in **Figure 8** may be implemented in a menu process, such as menu process 304 in **Figure 3**. The process in **Figure 8** is in response to a user selecting a pop-up menu item causing an actionPerformed method to be called. This process results in an ActionEvent object being passed in the callback. Java provides an interface which can be implemented to handle callbacks on menu item selection, button presses, etc. This interface is called the ActionListener interface. The fully-qualified name is java.awt.event.ActionListener. The one method in this interface is the actionPerformed method which receives an input parameter of type java.awt.event.ActionEvent. This ActionEvent object has the method getActionCommand, which returns a string for the menu item which is triggering the callback. In the present invention, when the actionPerformed callback is invoked, the code interrogates the ActionEvent object (via the getActionCommand method) to determine which pop-up menu item has been selected. Then, the user's selected action can be instantiated and executed. The object contains the string name of the Java class saved in the process described in **Figure 6** above.

In **Figure 8**, the process begins by retrieving the actionCommand for an action from the ActionEvent object passed in response to a selection of an action from menu item (step 800). The object, in this example, is a string version of the Java class as saved by the process

described in **Figure 6** above. The action class is instantiated based on the actionCommand passing the object of the pop-up to the new action class (step 802). Then, the action class is executed (step 804) with the process terminating thereafter. This action class performs the process or logic to execute the action selected by the user. The mechanism of the present invention may be implemented in other programming environments, such as C++. In the C++ environment, the process of the present invention may be performed using C++ Runtime-type identification (RTTI) to determine the class type and then use that type to find the related actions. Generally, if a type for an object can be obtained, the related actions for the object can be looked up.

Thus, the present invention provides an improved method, apparatus, and computer implemented instructions for identifying actions that may be performed by or on an object. This identification is a dynamic identification in which the association of the actions with an object may be different and dynamically presented at runtime. The menu logic of the present invention can dynamically determine differing menu items at runtime based on registered class-to-action relationships, but the registration of the items related to Java classes is performed prior to runtime. This mechanism allows associating actions with objects without requiring a hard-coded relationship. In this manner, new actions may be associated or existing actions may be unassociated with an object as needed. The present invention provides for extensibility, which allows the behavior of a running program to be extended without redesigning, reworking or

It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media, such as a floppy disk, a hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and transmission-type media, such as digital and analog communications links, wired or wireless communications links using transmission forms, such as, for example, radio frequency and light wave transmissions. The computer readable media may take the form of coded formats that are decoded for actual use in a particular data processing system.

30 The description of the present invention has been
presented for purposes of illustration and description,
and is not intended to be exhaustive or limited to the

Docket No. AUS920010498US1

invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Although the examples are discussed with respect to the Java programming language, the mechanism
5 of the present invention may be implemented in other programming languages, such as, for example, C. Also, the associations in these examples are identified at runtime. The embodiment was chosen and described in order to best explain the principles of the invention,
10 the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.

09895088-052904